MI

DESCRIPTION

PU integral (polyurethane) Back and Seat in different finishes, moulded over internal injected aluminium skeleton. Seat has also a spring to provide comfort. Model with Arms made from 13 mm thick hot-rolled steel cylindrical tube coated in epoxy 90 microns thickness and polypropylene armrest. Frame made from 13 mm thick hotrolled steel cylindrical tube coated in epoxy 90 microns thickness. Available in chromed finish. Polypropylene caps with anti-skid pad. Black finish.

BACK AND SEAT



(see finishes card)

MODEL WITH ARMS





Stackable chairs - max. 4 units - model with or without arms

1 PU integral back and seat

- (2) Internal skeleton, injected aluminium
- 3 Optional aluminium arm.
- 4 Aluminium frame seat with springs
- 5 Frame made from 12mm thick hot-rolled steel cylindrical tube
- 6 Caps of polypropylene (P.P) with anti-skid pad

SIZES


CANTILEVER


Total height: from 820 mm
Total width: from 460 mm
Total depth: from 510 mm

CANTILEVER STOOL

Total height: from 1130 mm Total width: from 460 mm Total depth: from 510 mm Seat height: from 430 mm Seat width: from 370 mm Seat depth: from 510 mm

Seat height: from 770 mm Seat width: from 370 mm Seat depth: from 510 mm





■ CANTILEVER STOOL







MATERIALS

Maximum use of materials to eliminate and minimize scraps. Use of recyclable and recycled materials in those components that do not affect the functionality and durability.



PRODUCTION

Maximum optimization of energy use. Minimal environmental impact. Last generation technological systems. Zero discharge of wastewater. No VOC coatings. Processes free of heavy metals, phosphates, OC and COD.

100% ALUMINIUM, STEEL & W00D



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.

100% RECYCLABLE PACKAGE AND THINNER FRFF



USE

Quality and warranty. Long lasting. Replacements available.

EASY TO CLEAN AND MAINTAIN



DISPOSAL

Waste reduction. Supplier-manufacturer packaging reuse system. Components are easy to be separated. Inks in packaging are water-based, without solvents.

RECYCLABLE

CERTIFICATES AND REFERENCES

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).



The mark of



PEFC Certificate

EN ISO 14006:2011 **ECODESIGN** Certificate



UNF-EN ISO 9001:2008 ISO 9001 Certificate



UNE-EN ISO 14001:2004 ISO 14001 Certificate



E1 Certificate by EN 13986



proyecto certificado LEED® GOLD por el U.S. Green Building Council en 2011 Leadership in Energy & Environmental Design

09

STANDARDS

MIT has passed tests done in our technical department as well as the tests done in AIDIMA the Technological Institute for furniture. The tests correspond to:

- BN -112-08:2005. Soiling and cleaning test.
- UNE-EN 15373:07. Furniture. Resistance, long lasting, security. Requirements for non domestic use seating.

- UNE-EN 1728:2001. Domestic furniture Seating Test methods for the determination of strength and durability.
- UNE-EN 16139:13. Furniture. Resistance, long lasting, security. Requirements for non domestic use seating.

4 Legs with writing tablet.

- UNE-EN 1728:2001. Domestic furniture Seating Test methods for the determination of strength and durability. Draughtsman chair.
- UNE-EN 1728:2001. Domestic furniture Seating Test methods for the determination of strength and durability. Beam seating.
- UNE-EN 1728:200. Domestic furniture Seating Test methods for the determination of strength and durability.
- UNE-EN 1022:05. Office furniture. Confident chairs.